



- WORKS ACCESS** **WORKS EXIT**
- To be agreed on site
- KEY**
- Cone
 - Sign
 - ▨ Work area
 - ▨ Safety zone
 - Hoarding
 - ▨ Pedestrian ramp (Fixed to ground)
 - ⬆ Traffic light head

DETAIL B

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.
 Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.
 Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:

- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
- 2) 45° tapered cones have 1.5m spacing, no relaxations.
- 3) On motorways and NLS AP roads with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C2

Single carriageway 40mph or less - 450mm traffic cones.
 Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:

- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.

For Installation:

Rev	Description	By	Chkd	Date
Revisions				

Client

BUCKINGHAM
Group Contracting

Project

**STATION APPROACH
KIDDERMINSTER
GIRD REF: 383807, 276330**

Title

**FENCED OFF
AREA 1
PHASE 4**

2 Tyburn Road
Erdington
Birmingham
B24 8NP

0121 326 9143
info@htmltd.co.uk
www.htmltd.co.uk

ATM
HIGHWAY TRAFFIC MANAGEMENT

Design: RS	Drawn: DM	Chkd: RS
Date: 08/08/18	Date: 08/08/18	Date: 08/08/18
Scale: NTS @ A3	Status: PROPOSED	
Drawing No	Rev:	
10626.004		